



■ SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 7A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000MΩ min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max

■ HOUSING

- Part No. : 2410-xx-R
└─ No. of poles
- Poles : 2-14
- Material : Nylon 66 UL94V-2
- Q' ty : 1,000 pcs./Bag

Poles	Dimensions(mm)	
	A	B
2	3.96	8.92
3	7.92	12.88
4	11.88	16.84
5	15.84	20.80
6	19.80	24.76
7	23.76	28.72
8	27.72	32.68
9	31.68	36.64
10	35.64	40.60
11	39.60	44.56
12	43.56	48.52
13	47.52	52.48
14	51.48	56.44



APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
林陳鏢	3:1	mm	.0 ±0.3	ECR	RoHS Compliant	07/01/04			
CHECKED BY	PROJ	VER NO.	.00 ±0.2						
			.000 ±0.1						
			ALL ±						
			ANGLE						
			0° ±						
			.0° ±						

PART NO 2410-xx-R
 3.96mm Crimp Style Connectors Housing

CUSTOMER
 ROHS COMPLIANT

DRAWN BY 余秀麗
 DATE 2005/05/15
 SIZE A4