


■ SPECIFICATIONS


- Voltage Rating : 125V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 500MΩ min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max

■ TERMINAL


- Applicate Wires : AWG# 18 - 24
- Material : Brass
- Finish : Tin Plated
- Thickness : 0.25mm
- Q' ty : 6,000 pcs./Reel



A-A SEC



B-B SEC



C-C SEC

gtk GTK UK LTD.

APPROVED BY

林陳樂

SCALE

4:1

UNIT

mm

TOLERANCE

.0 ±0.3 ECR

LTR

ECR

REVISION RECORD

DG 200607-001 06/07/25

DATE

06/09/21

LTR

REVISION RECORD

DG 200609-006 06/10/24

DATE

CHECKED BY

PROJ

VER NO.

.000 ±0.1 ECR

ECR

DG 200610-007 06/12/21

DATE

06/12/21

LTR

REVISION RECORD

DG 200612-007

DATE

PART NO 2410T-R

3.96mm Crimp Style Connectors Terminal

DRAWN BY

劉蓮花

DATE

2006/12/21

SIZE

A4

ANGLE

0° ±

.0° ±

LTR

REVISION RECORD

DATE

LTR

CUSTOMER

Conforms to The RoHS Instruction