


- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. GOLD PL 3 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
 3. GOLD PL 30 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
 4. BERYLLIUM COPPER PER QQ-C-530

RoHS COMPLIANT

					DIMENSIONS ARE IN MILLIMETERS				PART NO.		 GTK UK LTD.		
					UNLESS OTHERWISE SPECIFIED TOLERANCES (一般公差)				APPROVED	DATE			TITLE
INSULATOR	PTFE	WHITE			0.5~5	= ±0.2			<i>Jerry</i>	07/30/12'			SMA R/A PCB JACK
INSULATOR	PTFE	WHITE			>5~30	= ±0.4			<i>Jerry</i>	07/30/12'			DRAWING NO. SMA-J1T-GG25-R
BODY	NOTE 1	NOTE 2			>30~120	= ±0.6							
CONTACT PIN	NOTE 4	NOTE 3			>120~315	= ±1							
CUBE BODY	NOTE 1	NOTE 2			>315~1000	= ±1.5							
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	4/1	ISSUE	A2	DRAWN	DATE		
										<i>Alley</i>	07/30/12'		