



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. GOLD PL 3 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
3. GOLD PL 30 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
4. TEFLON MIL-P-19468
5. BRASS JIS H3250,C 3601

RoHS COMPLIANT

					DIMENSIONS ARE IN MILLIMETERS		PART NO.		
					UNLESS OTHERWISE SPECIFIED TOLERANCES (一般公差)		APPROVED <i>Jerry</i> DATE 01/30/12		
					0.5~5 = ±0.2		CHECKED <i>Ken</i> DATE 01/30/12		
					>6~30 = ±0.4		DRAWN <i>Polly</i> DATE 01/30/12		
					>30~120 = ±0.6		TITLE		
					>120~315 = ±1		SMC R/A PCB MOUNT JACK		
					>315~1000 = ±1.6		DRAWING NO.		
					ANGLES(角度) = ±5°		SMC-J1T-GG25-R		
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	4/1	ISSUE	A2
	INSULATOR		NOTE 4	WHITE					
	INSULATOR		NOTE 4	WHITE					
	BODY		NOTE 1	NOTE 2					
	CONTACT PIN		NOTE 5	NOTE 3					
	CUBE BODY		NOTE 1	NOTE 2					

