



FAKRA

specification sheet

Electrical characteristics		
Impedance		50 Ω
Maximum frequency		4 GHz
Working voltage	RG178	250 V _{RMS} max.
	RG316, 0.085"	335 V _{RMS} max.
Dielectric withstanding voltage	RG178	750 V _{RMS} min.
	RG316, 0.085"	1000 V _{RMS} min.
VSWR	Straight	1.3 max.
	Right angle	1.5 max.
Contact resistance	Centre contact	20 m Ω max.
	Outer contact	10 m Ω max.
Insulator resistance		1000 M Ω min.

Materials		
Part name	Material	Finish
Plastic housing	PA66 w/ 30% glass fibre	Colour coded
Body, metal parts	Brass per QQ-B-626	Nickel 70 μ "
Centre contact	Male	Brass per QQ-B-626
	Female	Beryllium copper per QQ-C-530
Insulator	Teflon	None
Crimp ferrule	Annealed brass	Nickel 70 μ "

Note: Other materials or finishes may be available on request

Mechanical & environmental characteristics	
Engagement force	25 N max.
Disengagement force	2 N max.
Contact retention	4 lbs min.
Durability (mating cycles)	25 cycles min.
Temperature range	-40 °C to 105 °C
Vibration	MIL-STD-202 method 204 test cond. B
Salt spray	MIL-STD-202 method 101 test cond. B
Thermal shock	MIL-STD-202 method 107 test cond. B